

BLISTER PACKING MACHINE



Silent Features

- Automatic & Most suitable machine for tablets, Capsules and Inject able packing.
- Fully automatic, High-Speed with continuous operation cycle mechanism for efficient packing.
- ✓ Fully automatic forming & sealing with manual & auto feeding.
- A comparatively lengthy 'Guide Track' for rigid inspection for missing filling, if any suitable for manual feeding.
- Crease proof sealing pattern to eliminate capillary formation of foil on Sealing and Knurling efficiency saves products from hygroscopic effects and ensures convenient passage through leak tests.
- Contact heating system with Pneumatic actuation allows Blister forming with even heating and save wastage of PVC after every stoppage.
- Universal type chain driven Batch Printing Unit.
- Adaptable to Change Parts of other machines of similar design.
- Intermo forming of Manufacturer's or Product's NAME (Optional).
- D.C/AC Drive: Crompton Greaves or any equivalent standard Make.
- Electronic Temp. Controller Selects or any standard Make.
- Electric Penal Components: L&T, Tecnik & Indo kopp or any equivalent standard Make.

Model		INJ-SPECTRA-I	INJ-SPECTRA-II
PVC Base Film.	Max. Width (mm)	120	220
	Max. Reel Diameter (mm)	400	440
	Max. Thickness (mm)	0.2 to 0.3	0.3 to 0.4
Aluminum Base Film.	Max. Width (mm)	115	210
	Max. Reel Diameter (mm)	200	210
	Max. Thickness (mm)	0.02 to 0.03	0.02 to 0.03
Packing Length	Maximum (mm)	110	195
Packing width	Maximum (mm)	100	100
Forming Depth	Maximum (mm)	12	12
Output Range	*No. Stroke/Minute	110	100
Power Requirements	3ph, 415V,AC Electric Supply	4.5 Kw	7.5 Kw

Technical Specification