

## ROTERY TABLET PRESS



### Silent Features

- ✔ In compliance with cGMP Standards.
- ✔ Paint free tablet manufacturing zone.
- ✔ Turret Made from special grade S.G. Iron casting.
- ✔ Digital Tablet cum RPM counters.
- ✔ Upper punch penetration system.
- ✔ Variable speed pulley drive.
- ✔ Overload pressure release arrangement.
- ✔ Interlocking system at Upper guards.
- ✔ Dust extraction nozzles with clamp.
- ✔ Reverse direction motion protection to avoid accident.

### Technical Specification

Model	SAMD-27	SAMB-27	SAMB-35	SAMB-45
Tooling	"D"	"B"	"B"	"BB"
No. of stations	27	27	35	45
Max. Output (Tab/Hr.)**	136,000	136,000	175,500	226,000
Operating Pressure	10 Tons	6.5 Tons	6.5 Tons	6.5 Tons
Max. Tablet Dia	25 mm	16 mm	16 mm	11 mm
Max. Depth of Fill	20 mm	17 mm	17 mm	17 mm
Turret Rpm	15 to 42	15 to 42	15 to 42	15 to 42
Electricals	5 HP, 3 Phase, 415 V, A.C.			

\*\* The max. Tablet output is depending upon the following factors.

- 1.The properties of material to be compressed
- 2.The tablet shape, weight and its thickness
- 3.Ambient Condition
- 4.Operator skills etc