

## Manufacturer & Exporter of Pharmaceutical Machinery

## TABLET COATING MACHINE



## Silent Features

- Ø GMP Model available in24"/ 36"/ 42"/ 48"/ 60"/ 72" Dia. Coating pans for conventional coating of tablet.
- Fitted with Hot Air Blower and also available optional separate Hot Air Blower system.
- Easy to replace a Polishing Pan instead of Coating Pan.
- *9* 36", 42", or 48" coating machine has variable speed drive and hot air blowing systems is built in the machine.
- 60" or 72" coating machine has variable speed drive and hot air separately on demand.
- Optional Spraying System can be provided for film coating with Peristaltic Pump, Spraying Nozzle with Stand and material handling container with stirrer.
- All Coating Machine are provided with interlocked electrical circuit so that heaters can be operated only after blowers are made "ON" to avoid burning of heaters.

Model	SACP12	SACP24	SACP36	SACP42	SACP48	SACP60	SACP72
Loading Capacity in Kg.	8	45	80	100	150	210	275
Motor H.P.	0.5	1	1.5	2	3	5	5
RPM of Pan .	30	10 to 30	10 to 30	10 to 25	10 to 25	10 & 12	8 & 10
Pan mounting angle deg.	30°	30°	30°	30°	30°	30°	30°
Blower motor H.P.	0.25	0.25	0.33	0.33	0.33	1	1
Blower capacity(Max CFM)	50/100	50/100	100/150	100/150	150/200	250/400	350/400
Heater capacity in K.W.	0.5	1.5	3	3	3	4	4

## **Technical Specification**